


7" HDMI Touch Screen Monitor

高清触摸液晶显示器

Model: SD639AHT



Model: SD619AHT



FEATURES HIGHLIGHTS:

- 4&5-wire resistive/ capacitive touch screen
- Built-in multi-language OSD
- Multiple inputs designed for multiple devices

产品特性:

- 4&5线电阻/电容式触摸屏
- 支持多语言菜单设置
- 多种信号输入, 连接各种设备

SPECIFICATIONS

	型号	Model	SD619AHT	SD639AHT
DISPLAY	屏幕	Panel	7" LED Backlit	7" LED Backlit
	触摸屏	Touch Screen	4&5-Wire Resistive Touch/ Capacitive Touch	4&5-Wire Resistive Touch
	触摸方式	Touch Interface	USB (RS232 for Optional)	USB (RS232 for Optional)
	分辨率	Resolution	1024×600 pixels	800×480 pixels
	亮度	Brightness	300cd/m ² / 600cd/m ² (Optional)	500cd/m ² / 1000cd/m ² (Optional)
	屏幕比例	Aspect ratio	16:9	16:9
	对比度	Contrast	800:1	500:1
FORMATS	可视角度	Viewing Angle	85°/85°(L/R) 85°/85°(U/D)	70°/70°(L/R) 50°/70°(U/D)
	HDMI 格式	HDMI Support Format	480i/480p/576i/576p; 720p/1080i/1080p(50/60Hz)	480i/480p/576i/576p; 720p/1080i/1080p(50/60Hz)
INPUT	输入	HDMI	1	1
		VGA	1	1
		AV	1	1
AUDIO	耳机孔	Earphone Slot	1	1
POWER	扬声器	Speaker	1	1
	消耗功率	Power Consumption	≤6W	≤6W
ENVIRONMENT	输入电压	Input Voltage	DC7-24V	DC12V±20%
	工作温度	Working Temperature	-20°C~55°C	-20°C~55°C
	储藏温度	Storage Temperature	-30°C~65°C	-30°C~65°C
	安装方式	Mounting Process	Stand Bracket VESA 75*75mm 1/4-20 Hole in the Bottom	Stand Bracket VESA 75*75mm 1/4-20 Hole in the Bottom
DIMENSION	单机尺寸	Unit Size	188.8L×128.7H×40.2D (mm)	184L×126H×32D (mm)
	单机重量	Unit Weight	535g	495g