


8" HDMI Touch Screen Monitor

高清触摸液晶显示器

Model: SD813AHT



Model: SD819AHT



FEATURES HIGHLIGHTS:

- 4&5-wire resistive/ capacitive touch screen
- Built-in multi-language OSD
- Multiple inputs designed for multiple devices

产品特性:

- 4&5线电阻/电容式触摸屏
- 支持多语言菜单设置
- 多种信号输入, 连接各种设备

SPECIFICATIONS

	型号	Model	SD823AHT(IPS Panel)	SD813AHT	SD819AHT	
DISPLAY	屏幕	Panel	8" LED Backlit		8" LED Backlit	
	触摸屏	Touch Screen	4&5-Wire Resistive Touch		4&5-Wire Resistive Touch	
	触摸方式	Touch Interface	USB (RS232 for Optional)		USB (RS232 for Optional)	
	分辨率	Resolution	1024×768 pixels	800×600 pixels	800×480 pixels	
	亮度	Brightness	350cd/m ²	250cd/m ²	300cd/m ² / 450cd/m ² (Optional)	
	对比度	Contrast	800:1	500:1	500:1	
	可视角度	Viewing Angle	85°/85°(L/R) 85°/85°(U/D)	70°/70°(L/R) 50°/70°(U/D)	70°/70°(L/R) 50°/70°(U/D)	
FORMATS	屏幕比例	Aspect ratio	4:3		16:9	
	HDMI 格式	HDMI Support Format	480i/480p/576i/576p;720p/1080i/1080p(50/60Hz)		480i/480p/576i/576p;720p/1080i/1080p(50/60Hz)	
INPUT	输入	HDMI	1		1	
		VGA	1		1	
		Video			2	
		Audio			1	
		DVI Input for Optional			1	
		AV	1		1	
AUDIO	扬声器	Speaker	1		1	
POWER	消耗功率	Power Consumption	≤6W		≤6W	
	输入电压	Input Voltage	DC12V±10%		DC 7-18V	
ENVIRONMENT	工作温度	Working Temperature	-20°C~55°C		-20°C~60°C	
	储藏温度	Storage Temperature	-30°C~65°C		-30°C~70°C	
	安装方式	Stand Bracket	Stand Bracket			Stand Bracket
		Mounting Process	Mounting Process	VESA 75*75mm 1/4-20 Hole in the bottom		VESA 75*75mm 1/4-20 Hole in the bottom
DIMENSION	单机尺寸	Unit Size	216L×149H×37D (mm)		208L×147H×33D (mm)	
	单机重量	Unit Weight	535g		535g	