



Model number	SD870-3250E-V	
chassis	Material/Structure	Aluminum alloy + sheet metal material, fanless heat dissipation
	colour	Iron gray + sand gray
	Dimensions (length, width and height)	153 * 128 * 64.1 MM
	Weight (bare weight)	1.1 KG
	Install	Desktop /DIN rail/Wall mount /VESA
Front panel interface	Switch	1* Power key with indicator light, 1* one key restore (and reset key to choose one), 1*ACLOSS (power on DIP switch)
	LED	1* hard disk indicator
	USB	1 x USB2.0, 1 x USB3.0
	Audio frequency	1*Line out, 1*Mic
	SIM	1*SIM standard card slot
	Phoenix terminal	1*4P(1* Power signal /1* Power indicator signal)
Rear panel interface	Display interface	1*VGA, 1*HDMI1.4
	COM	2*RS232/485 DB9 Serial port

	LAN	2*Intel I210AT Gigabit electrical port
	USB	2 x USB3.0, 2 x USB2.0
	Power interface	1*DC(5.5*2.5) or 1*3P P=5.08mm Phoenix terminal, support DC 9~36V wide voltage
store	SATA	1 x 2.5-inch hard disk
	MSATA	1*MSATA
	M.2	1*M.2/SSD, supports Key-M, 2280, NVME PCIE x4 SSDS
extend	M.2	1*M.2/5G, supports Key-B, 2242/52, 5G modules
	Wireless network card	Integrated WiFi(WiFi model based on NUC module)
Power supply type input	Power supply type	External power adapter
	Voltage input	DC 9-36V
	Power output	AC TO DC more than 60W
environment	Operating temperature	-10°C to 50°C
	Storage temperature	-20°C to 70°C
	Relative humidity	5%-95% relative humidity, no condensation
	Working vibration	0.5g rms/5-500HZ/random/operating

