



Product model	SD890-30SL_6L
processor	Integrated Haiguang C86 3350 processor 3.0GH 8 core 16 threads TDP 65W
chipset	SOC
Internal memory	4*DDR4 UDIMM memory slot, support up to 3200MHz DDR4 memory, support up to 128GB,
display	1* VGA port (This port is an IPMI display port and requires IPMI function)
network	6* Intel® WGI210AT Gigabit network adapter, support network wake up, PXE functions 1*RTL8211F Gigabit network adapter, support network wake up, PXE (IPMI management port)
Store	3* SATA 3.0 hard disk interface,SATA interface transmission speed up to 6Gbps
	1* M.2 slot, supporting the M.2 Key M 2260/2280 SATA SSD standard
Tone	N/A

frequency	
Expansion slot	1* Mini-PCIE slot with WIFI support
	2 x PCIE X8 gold finger
I/O ports on the backplane	1* RJ45 serial port
	2* USB3.0 interface (5Gbps)
	6* RJ45 Gigabit network interface
	1* Power switch, 1* reset switch
	1* Power indicator, 1* hard disk indicator
Built-in I/O interface	1* JVGA port 1*12pin(IPMI display port)
	1* RS232 serial port, 2*5pin
	2* USB 3.0 interface 2*10Pin
	1* TPM interface, 2*6pin
	1* Front panel function button and indicator port 2*5pin
	1* LPC interface 2*5pin
	1* Network indicator port 2*13pin
	1* PS/2 keyboard and mouse interface 1*6pin
	1 x network pin port 2 x 6pin(IPMI management port)
	1* 24pin ATX power input interface
	1* 8pin ATX power input interface
	Fan interface
BIOS	128Mb Flash ROM
Operating system	Windows 10/Windows 11/Linux
Guard dog	Support hardware reset function (256 level, 0~255 seconds)
Power supply type	ATX power input
Operating temperature	0°C to 60°C
Storage temperature	-20°C to 70°C

Working
humidity

5%-95% relative humidity, no condensation

Size

220mm x 280mm

