



Product model	<b>SD890-250M3 (I210AT)</b>
processor	<b>6th/7th/8th/9th Celeron/Pentium/Core™ i3/i5/i7 processors supporting the LGA1151 architecture, Note: Support 6/7/8/9 generation 95W CPU</b>
chipset	<b>Intel Q250 high-speed chipset</b>
Internal memory	<b>2 x DDR4 DIMM slots for dual-channel 2133 MHZ memory, 2400 MHZ memory, and 2666 MHZ memory, with a maximum capacity of 64GB Integrated Intel® HD Graphics controller with 1*VGA port and 1*HD OUTPUT1.4 port</b>
display	<b>Supports single display, dual display mode, and extended mode</b>
network	<b>2* Intel I210AT Gigabit network adapter, supporting network wake up and PXE functions</b>
deposit	<b>4* SATA3.0 hard disk interface, SATA transmission speed up to 6Gbps</b>
	<b>1* MSATA interface, support Intel protocol SSD, transmission rate up to 6Gbps</b>
	<b>1* M.2 slot, supporting the M.2 2280 PCIE x4/SATA adaptive standard SSD</b>
Tone	<b>Onboard ALC888S high fidelity audio controller, support Mic, Line</b>

frequency	<b>out, line-IN</b>
Expansion slot	<b>1 x PCIE x16 slot</b>
	1 x PCIE x4 slot
	2* PCI slot
I/O ports on the backplane	<b>1* PS/2 keyboard and mouse interface</b>
	1 * VGA display port
	1*HD OUTPUT display interface
	2* RS232 serial port (COM1/2 supports 5V/12V live function, COM1/2 supports RS485/422 function)
	2* RJ45 Gigabit network interface
	2* USB 2.0 port
	4* USB 3.0 interface
	1*Line out interface (green), 1* Mic interface (red), 1* Line-IN interface (blue)
Built-in I/O interface	<b>1* PS/2 keyboard and mouse interface 1*6pin row pin and UK1 signal</b>
	1* JVGA port 1*12pin pin row, same signal as DB15
	4 x RS232 serial port 2 x 5pin row pins
	1* front audio interface 2*5pin row pins
	4* USB 2.0 port 2*5Pin row pins
	1*USB2.0 port USB TYPE-A
	1* TPM port 2*8pin row pins
	1* Front panel function buttons and indicator ports 2*5pin row pins
	1*LPT 2*13 pin row
	1* 24pin ATX power input interface
	1* 8pin ATX power input interface
Fan interface	<b>1*4pin CPU intelligent fan interface, 3* 4pin system intelligent fan interface</b>
BIOS	<b>64Mb Flash ROM</b>
Operating system	<b>Windows 7 / 10 / Linux</b>
Guard dog	<b>Support hardware reset function (256 level, 0~255 seconds)</b>
Power	<b>ATX power input</b>

supply type	
Operating temperature	<b>0°C to 60°C</b>
Storage temperature	<b>-20°C to 70°C</b>
Working humidity	<b>5%-95% relative humidity, no condensation</b>
dimension	<b>245mm x 220mm(mATX)</b>

