



Model No.	SD890-320E V1.0(B250)	
Case	Material/Structure	1U rack mount case, high quality galvanized steel case
	Color	Iron Gray
	Dimension	L430MM*W320MM*H44.5MM
	Installation	1U rack mount
Motherboard	CPU	Support LGA1151 6th/7th/8th/9th Celeron/Pentium/Corei3/i5/i7/i9 series processor
	Chipset	Intel B250 Express chipset
	Graphics	Integrated Intel®HD Graphics
	Memory	2* DDR4 DIMM RAM slot, 2133/2400/2666MHz, up to 64GB
Front Panel I/O	POWER	1*Power switch, 1*Reset switch
	USB	2* USB2.0
	LAN	6*Intel WGI211AT Gigabit Ethernet, support Wake On LAN、PXE function
	SFP Port	Support 2* Gigabit SFP or 2* 10Gigabit fiber port (expansion)
	COM	1* RS232 COM port
	LED	1* HDD LED, 1*Power LED, 4*SFP LED, 2*data transfer LED
Rear Panel I/O	Display Port	1*VGA port
	Power Port	1*AC power port
Storage	SATA	2* 2.5"SATA port
Expansion	Mini PCIE	1* PCIE X8 slot, for 1G, 10GB SFP card expansion

OS Support	Microsoft Windows	Windows 7(not include OS code)
	Linux	Ubuntu
Power Type		AC 220V 1U ATX 250W
Environment	Working Temp.	-10℃~60℃
	Storage Temp.	-20℃~70℃
	Relative Humidity	5%-95% relative humidity, non-condensing
	Working Vibration	0.5g rms/5-500HZ/random/operating
Environment	Operating Temp.	-10℃~60℃
	Storage Temp.	-20℃~70℃
	Relative Humidity	5%-95%(Relative humidity, no condensation)
	Working Vibration	0.5g rms/5-500HZ/random/operating
Environment	Operating Temp.	-10℃~60℃
	Storage Temp.	-20℃~70℃
	Relative Humidity	5%-95% relative humidity, non-condensing
	Working Vibration	0.5g rms/5-500HZ/random/operating
	Relative humidity	5%-95% relative humidity, no condensation
	work vibration	0.5g rms/5-500HZ/random/operating



