



Model No.	SD890-280E V1.0(5205U)	
Case	Material/Structure	1U standard case, high quality galvanized material
	Color	Light silver black
	Dimension(L*W*H)	430* 280.2*45MM
	Installation	1U standard rack mounting method
Motherboard	CPU	Onboard 10th Gen Celeron 5205U 1.9GHz dual Core 2 thread processor, TDP 15W
	Chipset	SOC
	Graphics	Intel®HD Graphics
	Memory	2* DDR4 SODIMM RAM slot, 2400MHz , max up to 64GB
Front Panel Port	POWER	1* Power switch, 1* Reset switch
	LAN	6* WGI211AT Ethernet, support Wake On LAN / PXE
	COM	1* RJ45 COM port
	USB	2* USB2.0
	LED	1* HDD LED, 1*Power LED
Rear Panel Port	Display Port	1*VGA port
	Power	1* power supply connector
Storage	SATA	N/A
	SSD	1* MSATA slot, support Intel protocol SSD, transfer rate up to

		6Gbps
Expansion	Mini PCIE	N/A
	M.2	1* M.2 Key-B slot, support M.2 2230/2242/2252 4G/5G module
OS Support	Microsoft Windows	Windows® 7/ 10/Linux
	Linux	Ubuntu
	Watch Dog	Support hardware reset function (L256, 0~255 seconds)
Power Supply	Power type	Open power supply
	Relative Humidity	5%-95% relative humidity, non-condensing
	Working Vibration	0.5g rms/5-500HZ/random/operating
Environment	Operating Temp.	-10℃ ~60℃
	Storage Temp.	-20℃ ~70℃
	Relative Humidity	5%-95%(Relative humidity, no condensation)
	Working Vibration	0.5g rms/5-500HZ/random/operating
Environment	Operating Temp.	-10℃ ~60℃
	Storage Temp.	-20℃ ~70℃
	Relative Humidity	5%-95% relative humidity, non-condensing
	Working Vibration	0.5g rms/5-500HZ/random/operating
	Relative humidity	5%-95% relative humidity, no condensation
	work vibration	0.5g rms/5-500HZ/random/operating



