



Model number	SD870-205Z	
chassis	Material/Structure	Active cooling structure, galvanized steel material
	colour	Industrial control milky white
	Dimensions (length, width and height)	230mm*234mm*156mm
	Weight (bare weight)	KG
	Install	Desktop /4U rack type
Front panel interface	Switch	1* Power switch, 1* reset key
	LED	1* Power indicator, 1* hard disk indicator

	USB	2 * USB2.0
Rear panel interface	Display interface	1*VGA, 1*HDMI
	LAN	2*RJ45
	COM	2*RS232/485/422 DB9 COM, 4*RS232 DB9 serial port can be added
	USB	6*USB(USB3.0/2.0 quantity based on motherboard)
	PS/2	1*PS/2 keyboard and mouse interface
	Audio frequency	1*Line out(green), 1*MIC(red)
	Phoenix terminal	1*4P Phoenix terminal (including power signal, power indicator signal)
	GPIO	4 in 4 out (Optional, not supported on some motherboards)
store	SATA	1 x 3.5-inch hard disk or 1 x 2.5-inch hard disk
	MSATA	1*MSATA
extend	PCIE	1*PCIE X16
Power demand	Power supply type	Built-in small 1U FLEX power supply
	Voltage input	AC 110-220V
environment	Operating temperature	-10℃ to 50℃
	Storage temperature	-20℃ to 70℃
	Relative humidity	5%-95% relative humidity, no condensation
	Working vibration	0.5g rms/5-500HZ/random/operating



