



Model number	<b>SD870-570H-E1</b>	
chassis	<b>Material/Structure</b>	1U standard chassis, aluminum alloy panel, high quality galvanized steel plate
	colour	<b>Argentous black</b>
	Dimensions (length, width and height)	<b>430 MM * 320 MM * 44.5 MM</b>
	Weight (bare weight)	<b>4.5 KG</b>
	Install	<b>1U standard rack</b>
Front panel interface	<b>POWER</b>	1* Power switch, 1* reset switch
	LED	<b>1* hard disk indicator, 1* power indicator</b>
	USB	<b>2 * USB2.0</b>

Rear panel interface	<b>Display interface</b>	1*VGA, 1*HDMI
	COM	<b>2*RS232/485/422 DB9 serial port, can be expanded 4*RS232 DB9 serial port (optional)</b>
	LAN	<b>2*RJ45</b>
	USB	<b>6*USB(USB3.0/2.0 quantity based on motherboard)</b>
	PS/2	<b>1*PS/2</b>
store	<b>SATA</b>	Supports 1 x 3.5-inch hard disks or 1 x 2.5-inch hard disks
extend	<b>PCIE</b>	1*PCIE X16
Power source	<b>Power supply type</b>	Built-in small 1U FLEX power supply
	Voltage input	<b>AC 110-220V</b>
environment	<b>Operating temperature</b>	-10°C to 50°C
	Storage temperature	<b>-20°C to 70°C</b>
	Relative humidity	<b>5%-95% relative humidity, no condensation</b>
	Working vibration	<b>0.5g rms/5-500HZ/random/operating</b>



