



Model number	SD870-6750S-D2	
chassis	Material/Structure	Aluminum alloy + sheet metal material, fanless heat dissipation
	colour	Iron gray + sand gray
	Dimensions	185 * 163.4 * 48.5 MM
	Weight (bare weight)	KG
	Install	Desktop/wall-mounted /DIN rail
Front panel interface	Switch	1* Power button, 1* one key restore (and reset key to choose one), 1*ACLOSS (power on DIP switch)
	LED	1* hard disk indicator, 1* hard disk indicator
	USB	2 * USB2.0
	Audio frequency	1*Audio, Line out&Mic 2-in-1
	Phoenix terminal	1*4P(including 1* power signal /1* power indicator signal)
	SIM	1*SIM standard card slot
Rear panel	Switch	1*CMOS restore key

interface	Display interface	1*HD OUTPUT2.0, 1*HD OUTPUT1.4, 1*VGA, supports three displays
	COM	2*RS232/485 DB9 serial port, CAN support CAN(CAN module needs to be loaded)
	LAN	2*Intel I210AT Gigabit electrical port
	USB	2 * USB3.0, 2 * USB2.0
	Dip switch	2 sets of 6-bit dip switches, RS232/485 switching use
	Power interface	1*DC 12V(5.5*2.5)
store	MSATA	1*MSATA
	M.2	1*M.2/SSD, supports Key-M, 2280, NVME PCIE x4 SSDS
extend	MINIPCIE	1*MINIPCIE, support WiFi/4G module
Power supply type input	Power supply type	External power adapter
	Voltage input	DC 12V
	Power output	AC TO DC more than 60W
environment	Operating temperature	-10°C to 50°C
	Storage temperature	-20°C to 70°C
	Relative humidity	5%-95% relative humidity, no condensation
	Working vibration	0.5g rms/5-500HZ/random/operating

