



model	SD890-19SLZ	
Chassis	Material/Structure	1U standard chassis, high quality galvanized steel
	color	Asian silver black
	Size (length, width and height)	430mm*281mm*45mm
	Install	1U standard rack
motherboard	CPU	Integrated Intel® Celeron® J1900 2.0GHz quad-core processor, TDP10W
	system chip	Based on Intel® Bay trail SOC platform
	Display	Integrated Intel® HD Graphics Core Graphics
	Memory	1* SODIMM memory slot, support single channel 1600/1333MHz DDR3L/1.35V memory, maximum support 8GB
Front panel interface	POWER	1*Power switch, 1*Reset switch
	USB	2* USB2.0 interface
	COM	1* standard RS232 serial interface
	LAN	6* Intel WGI211AT Gigabit LAN, support Wake-on-LAN, PXE function,
	led	1* power indicator, 1* hard disk indicator
rear panel interface	display interface	1*VGA interface

	power supply	1*AC power input interface
storage	SATA	1* SATA2.0 2.5-inch notebook hard drive bay, you can directly install the hard drive
	SSD	1* MSATA SSD solid state drive expansion, SSD transfer speed up to 3Gbps
expand	Mini PCIE	2* Mini PCIE slot, support WIFI/3G/4G module
software support	Microsoft Windows	Windows 7/10, 64bit (without key)
	Linux	Ubuntu
	Watch Dog	Support hardware reset function (256 levels, 0~255 seconds)
power requirements	Power Type	External open power supply
	Voltage input	AC 110~220V
	power output	AC TO DC, 60W
surroundings	Operating temperature	-10°C ~60°C
Environment	Operating Temp.	-10°C ~60°C
	Storage Temp.	-20°C ~70°C
	Relative Humidity	5%-95% relative humidity, non-condensing
	Working Vibration	0.5g rms/5-500HZ/random/operating
Environment	Operating Temp.	-10°C ~60°C
	Storage Temp.	-20°C ~70°C
	Relative Humidity	5%-95% relative humidity, non-condensing
	Working Vibration	0.5g rms/5-500HZ/random/operating
	Relative humidity	5%-95% relative humidity, no condensation
	work vibration	0.5g rms/5-500HZ/random/operating



